
CAD MODEL



ASSEMBLY DRAWING





www. customvinyl.net

Locally Owned & Operated Products Certified 100% Lead Free

FEATURES and BENEFITS

- Impact rated grade 50 performance.
- Continuous head and sill with integral mullion.
- All Welded, Brickmold look, with J-Channel, slopped sill.
- Sweep lock no keeper needed. Passes forced entry.
- 3/4" glass capability or 5/8".
- Full 1-1/2" integral nail fin.
- Dual weatherstripping.
- Long reach interlock. No colliding or missing.
- Double wall frame for less roll.
- Universal pivot shoe pocket with Constant force balancesystem.
- Interior glazed fixed lite for easy drywall pass-throughcapability.
- Drywall pass through clip also used in integral mullion.
- Full family of Single Hung, Single Slider, and Picture Window.











MANUFACTURING LIMITATIONS

BASELINE PERFORMANCE			
Thermal Insulation			
GLASS	Uc Value	R Value	SHGC
LoE 270	0.30	3.33	.27
LoE 366	0.30	3.45	.20
LoE 366 w/i89	0.25	4.00	.20
Structural Performance			
Air Infiltration @ 25 mph		0.15 cfm/ft ²	
Water Penetration		7.50 psf	
Uniform Loads		+/-75.00 psf	

AAMA RATING: R-PG50-H