

Brio[®] Premiere

Brio 3000U Premiere Series Point of Use Cooler

STYLISH - CONTEMPORARY - CONVENIENT

Ideal for offices and public spaces, this Brio free-standing cooler is better equipped, well-thought out, and beautifully designed. Enjoy bottle water quality with none of the cost and help save the environment with the Brio Premiere 3000U hot and cold point of use water cooler. The exterior features a finger-print resistant finish that can stand up to any dirty hands. Did we mention it's really easy to clean? This model is ideal to use in any environment whether at home or in the office.



HOT & COLD



POINT OF USE



ENERGY STAR



UL LISTED



COMPRESSOR INSIDE

LG



Features:

- High-efficiency compressor with the lowest cycle rate available ensures a long lifespan
- Convection cooling with internally spring mounted, hermetically sealed compressor with automatic overload protector
- High-volume, 304 electro polished stainless steel hot and cold tanks with internal heating coils and copper refrigerant lines ensure no off taste to water
- Modern appliance styling; complements any décor
- Ergonomically placed spigots for easy dispensing
- .85-gallon cold water tank and .33-gallon hot tank ensures plenty of cold and hot water is always available
- Proprietary technology provides energy efficiency, reliability and low noise
- Removable drip tray for easy cleaning
- Innovative anti-leak system prevents improper filter installation
- Available in white, black, or wine red.

Technical Specifications:

The Premiere Series Brio Coolers offer high quality components, Longevity, Durability, and a simplistic built made precisely to cut costs on servicing equipment. All Premier Series Brio Coolers come standard with an *LG® high-efficiency compressor, which offers the lowest cycle rate available in the industry. *Rust and corrosion free. *Built with heavy gauge material frames and with commercial grade steel construction which allows it to become the most durable coolers in the industry.

Drip Tray:

One piece ABS drip tray is easily removed for cleaning

Hot Water Tank:

All stainless water reservoir with SUS 304 and SUS 316L Heater
Electropolished 1.25 Liters

Cold Water Thermostat:

Temperature is controlled to 39.2°F-53.6°F (4°C-12°C)

Refrigeration Unit:

R134a Convection cooled condenser, internally spring mounted hermetically sealed compressor with automatic overload protector. No lubricant needed. Refrigerant is controlled by accurately calibrated capillary tube. Quiet operation by the optimum design. Highly efficient cooling function

Compressor:

LG® high-efficiency compressor, which offers the lowest cycle rate available in the industry. Better energy, quiet operation, and durability

WARNING: The hot water is heated to approximately 90°C (194°F). Temperatures above 52°C (125°F) can cause severe burns from scalding. DO NOT ALLOW CHILDREN TO USE THE HOT WATER DISPENSING BUTTON WITHOUT PROPER AND DIRECT SUPERVISION.

Specifications	
Item Number:	CLW3000U (White)
	CLB3000U (Black)
	CLR3000U (Wine Red)
Function:	Hot & Cold (POU)
Power Supply:	AC 115V 60HZ
Net Dimension:	10.5" x 18" x 43.5"
Net Weight:	48 lbs.
Cold Tank:	
Volume of Tank:	3.2L (.85 Gallons)
Consumption:	100W
Capacity:	9.2°F~53.6°F
Hot Tank:	
Volume of Tank:	1.25L (.33 Gallons)
Consumption:	500W
Capacity:	176°F-194°F



Removable drip tray



Large dispensing area



7539 Pioneer Way, Suite A

Bozeman, MT 59718

Tel: (406) 582-4411

purewatertechnologies.com